



draft  go[®] 

Enjoy full
draught flavour
everywhere.



Sustainable.
Universal.
Flexible.



Universal application

draft2go+ is an innovative, self-sufficient dispensing system with a stainless steel dispense head and an integrated CO₂ chamber inside the KEG. This sustainable, reusable container is the perfect solution for breweries and wine businesses planning to extend their range. Draft2go+ will make it easier for them, as well as hospitality and catering businesses, to offer their guests a wide choice of beverages in premium quality – even in the smallest of spaces and completely independent of power and CO₂ supply.

Easy handling

The system uses the standard coupler range, covering all usual fitting types on the dispensing equipment market. The dispense head is easy to assemble and disassemble, which means hygiene is guaranteed at all times. With the help of the compensator, the flow rate can be adjusted easily. The attached, external pressure reducer with non-return valve keeps the carbon dioxide content in the drink at the optimum level.

The highly efficient, stylish insulator jacket will keep the pre-chilled beer at drinking temperature for up to 8 hours – ideal for dispensing full draught flavour, wherever you want to.

draft2go+ is the mobile alternative to stationary dispensing equipment and can be put to a universal range of uses.



Depending on the requirements, different stainless steel tap heads are available for the four fitting types: flat, basket, Grundy and draft fitting.



Flat fitting



Grundy fitting



basket fitting



draft fitting

The benefits

- Fresh draught flavour and perfect dispensing quality
- Food-safe, sustainable and reusable container guarantees perfect hygiene
- Highly efficient beer flow of up to 90 l / h possible
- Self-sufficient, environmentally friendly system, independent of power and CO₂ supply
- Consistently high beer quality for up to 28 days, so even residual contents remain in premium quality.
- Icepack, insulator jacket, cooling pad and cooling bag can reduce the beverage temperature to 2.5 degrees in 3 hours
- Can be filled on existing filling equipment

The PLUS side



- Strong and unbreakable dispense heads made of sustainable stainless steel, no plastic line required.
- Fits all commercially available KEG types
- Different fitting types available, enabling use in many different countries
- All parts can be dismantled easily for cleaning
- Compensator to regulate the flow rate
- Tap with spring and thread for positioning

The perfect system

draft2go[®] +



Sustainable, reusable KEG with dual-chamber system, flat fitting and standard CO₂ valve; can be used in conventional dispensing equipment, volume: 10 litres



Stainless steel dispense head with pressure reducer and tap handle



3-part insulator jacket keeps pre-chilled beer cold for up to 8 hours



Stainless steel drip tray for standing glasses on and hygienically catching beverage residues



No electric power needed



Scope of delivery

System package

- 1 Insulating base
- 1 Drip tray with grill
- 1 Insulating jacket
- 1 Dispense head of choice

Icepack set

- 1 ice sleeve
- 2 ice packs
- 1 cooler bag

Technical data

KEG	
Volume	10 l
Weight	approx. 5 kg
Height / external	Ø 394 mm / 253 mm
Material, stainless steel liner	standard: mat. no. 1.4301, AISI 304
Top and bottom rings	polypropylene (PP), UV stabilised, can be recycled
PP colour	standard: black, other colours on request
Neck and fitting	flat fitting
Operating overpressure	max. 3 bar beverage chamber; max. 7 bar CO ₂ chamber
Test pressure	approx. 9 bar overpressure

Safety bursting point	25 ± 7 bar overpressure, both chambers have a safety bursting point
Numbering	standard, lasered
Coding (options)	datixPLUS character code / transponder / barcode
Ecology	Reusable system, all parts can be recycled

draft2go+ dispensing system

Weight of entire system	approx. 10.5 kg
Height / width / depth	600 mm / 360 mm / 480 mm
Insulator jacket material	EPP (expanded polypropylene)

[Video tutorial](#)



SCHÄFER
CONTAINER SYSTEMS



SCHÄFER Werke GmbH
Pfannenbergstraße 1 · D-57290 Neunkirchen
Tel. +49 (0) 2735/787-481 · Fax +49 (0) 2735/787-493
E-Mail: info@schaefer-container-systems.de
www.schaefer-container-systems.com

[More information:](#)

